


Database Technology Entity Relationship Models




Previously on Database Technology

- Introduction to Relational Databases
 - A standard model for storing data
 - Using relations/tables
- Introduction to SQL
 - Creating and changing tables
 - Reading and writing data into tables



Today

- Designing databases
 - i.e., how to get from your customer's requirements...
 - ...to a set of tables and attributes



Outline

- Design Process
- Modeling
- Constraints
- E-R Diagrams
- Design Issues
- Weak Entity Sets
- Extended E-R Features
- Reduction to Relation Schemas
- Comparison UML

Database Design

- Initial phase: requirements engineering
 - characterize fully the data needs of the prospective database users
 - which data needs to be stored?
 - ...and in which volumes?
 - which queries should be answered?
- Conceptual schema
 - which types of entities and relations exist?
 - what attributes do they have?

Database Design

- Final phase: from a conceptual to physical data model
 - Logical Design: find a “good” collection of relation schemas
 - Business decision – What attributes should we record in the database?
 - Computer Science decision – What relation schemas should we have and how should the attributes be distributed among the various relation schemas?
 - Physical Design – Deciding on the physical layout of the database

Database Design Approaches

- Entity Relationship Model (today)
 - Models an enterprise as a collection of *entities* and *relationships*
 - Entity: a “thing” or “object” in the enterprise that is distinguishable from other objects
 - Described by a set of *attributes*
 - Relationship: an association among several entities
 - Represented diagrammatically by an *entity-relationship diagram*
- Normalization Theory (next lecture)
 - Formalize what designs are bad, and test for them

Entity Relationship Model

- Dates back to the 1970s
 - Chen, Peter Pin-Shan: *The Entity–Relationship Model – Toward A Unified View of Data*. ACM Transactions on Database Systems. 1(1): 9–36, 1976
 - developed to facilitate database design by allowing the specification of an enterprise schema that represents the overall logical structure of a database
- Toolkit for mapping the meanings and interactions of real-world enterprises onto a conceptual schema
- The ER data model employs three basic concepts:
 - entity sets,
 - relationship sets,
 - attributes
- Associated diagrammatic representation (ER diagram)
 - graphic expression of the overall logical structure of a database



Entity Sets

- An entity is an object that exists and is distinguishable from other objects
 - Example: Peter Chen, Mannheim, Star Wars
- An entity set is a set of entities of the same type that share the same properties
 - Example: set of all persons, cities, movies
- Each entity is represented by a *set of attributes*
 - Example:
instructor = (ID, name, street, city, salary)
course= (course_id, title, credits)
- A subset of the attributes form a *primary key* of the entity set i.e., uniquely identifying each member of the set

Entity Sets – Example

- instructor (instructor_id, instructor_name)
- student (student_id, student_name)

76766	Crick
45565	Katz
10101	Srinivasan
98345	Kim
76543	Singh
22222	Einstein

instructor

98988	Tanaka
12345	Shankar
00128	Zhang
76543	Brown
76653	Aoi
23121	Chavez
44553	Peltier

student

Relationship Sets

- A **relationship** is an association among several entities

Example:

44553 (Peltier) *advisor* 22222 (Einstein)
student entity relationship set *instructor* entity


- A **relationship set** is a mathematical relation among $n \geq 2$ entities, each taken from entity sets

$\{(e_1, e_2, \dots, e_n) \mid e_1 \in E_1, e_2 \in E_2, \dots, e_n \in E_n\}$
where (e_1, e_2, \dots, e_n) is a relationship

- Example:


$(44553, 22222) \in \textit{advisor}$

Relationship Sets



Relationship Sets

- An attribute can also be associated with a relationship set
- E.g., *advisor* relationship set:
 - date which captures the start of the supervision



Degree of a Relationship


- Definition: degree of a relationship
 - i.e., number of entity sets that are involved in relation set
- binary relationship (degree two)
 - involve two entity sets
 - the by far most frequent case
- Relationships between more than two entity sets (degree >2)
 - e.g.: students work on projects under the guidance of an instructor
 - relationship proj_guide is a *ternary relationship* between instructor, student, and project
 - those are rather rare

Cardinality Constraints

- Express the number of entities to which another entity can be associated via a relationship set
 - Most useful in describing binary relationship sets
- For a binary relationship set, the mapping cardinality must be one of the following types:
 - 1:1 (one to one)
 - 1:n (one to many)
 - n:1 (many to one)
 - n:m (many to many)

Mapping Cardinalities – One to One


- One to one (1:1)
 - Note: Some elements in A and B may not be mapped to any elements in the other set
- Examples
 - student_works_on_thesis
 - person_married_to_person



same entity set –
still binary!


Mapping Cardinalities – One to Many

- One to many (1:n)
 - Note: Some elements in A and B may not be mapped to any elements in the other set
- Examples
 - building_has_room
 - course_has_part




Mapping Cardinalities – Many to One

- Many to one (n:1)
 - Note: Some elements in A and B may not be mapped to any elements in the other set
- Examples
 - `course_takes_place_in_room`
 - `lecturer_works_in_department`



Mapping Cardinalities – Many to Many

- Many to many (n:m)
 - Note: Some elements in A and B may not be mapped to any elements in the other set
- Examples
 - student_takes_course
 - student_has_advisor



Distinguishing 1:n/n:1 and n:m Cardinalities

- Rule of thumb
 - Always ask for the cardinality the other way around
- “A building may have multiple rooms...”
 - “...but can a room be in multiple buildings?”
 - No → building_has_room is 1:n
- “A department can be located in multiple buildings...”
 - “...but can a building host multiple departments?”
 - Yes → department_located_in_building is n:m

Relation Sets from the Same Entity Set


- The two entity sets in a relation set may be the same
- This holds independently from the cardinality!
- person_married_to_person
 - 1:1
- person_is_father_of_person
 - 1:n
- person_has_father
 - n:1
- person_is_parent_of_person
 - n:m

Attribute Types & Domains


- Attribute types:
 - Simple and composite attributes
 - Single-valued and multi-valued attributes
 - Example: multi-valued attribute: phone_numbers
- Derived attributes
 - Can be computed from other attributes
 - Example: age, given date_of_birth
- Domain – the set of permitted values for each attribute

Composite Attributes

composite
attributes



component
attributes



Redundant Attributes

- Suppose we have entity sets:
 - instructor, with attributes: ID, name, dept_name, salary
 - department, with attributes: dept_name, building, budget
- In ERM, instructors and departments are connected by a relation set
 - e.g., instructor_belong_to_department (ID,dept_name)
- Now, dept_name is no longer needed in the instructor entity set
 - It is redundant there
 - Hence, we will remove it
- *Note:* sometimes, removed redundant attributes are reintroduced when converting the conceptual model into a logical model

Weak Entity Sets



- Consider the set of buildings and rooms
 - Entity set building(building_name,address)
 - Entity set room(number,capacity)
 - Relation set room_in_building (number,building_name)
- Note:
 - As in the previous example, we have removed the redundant attribute *building_name* from the entity set *room*
- Question:
 - What is the primary key of the the entity set *room*?

Weak Entity Sets

- Weak entity sets are entity sets that
 - do not have a set of attributes sufficient to identify each entity uniquely
 - require an additional relation set to identify each entity uniquely
- Those relation sets are called *identifying relation set*
- Weak entities do not have primary keys
 - A weak entity set has an *identifying entity* and a *discriminator*
 - Example:
 - *building* is the identifying entity
 - *number* is the discriminator
- A weak entity cannot exist without the identifying entity
 - e.g., a room cannot exist without the building


ER Diagrams

- Entity Relationship Diagrams (ER diagrams)
 - are the graphical notation of entity relationship models
- Notation of entity sets:
 - Rectangles represent entity sets
 - Attributes listed inside entity rectangle
 - Underlining indicates primary key attributes




ER Diagrams

- Diamonds represent relationship sets




ER Diagrams

- Diamonds represent relationship sets
 - Attributes can be attached to relationship sets




Roles

- Entity sets of a relationship need not be distinct
 - i.e., there may be a relationship set involving the same entity set twice
- Each occurrence of an entity set plays a “role” in the relationship
 - The labels “*course_id*” and “*prereq_id*” are called **roles**




Cardinalities in ER Diagrams

- We express cardinality constraints by drawing either a directed line (\rightarrow), signifying “one,” or an undirected line (—), signifying “many,” between the relationship set and the entity set.
- One-to-one relationship between an instructor and a student :
 - A student is associated with at most one instructor via the relationship advisor
 - A student is associated with at most one department via stud_dept




Cardinalities in ER Diagrams

- one-to-many relationship between an *instructor* and a *student*
 - an instructor is associated with several (including 0) students via *advisor*
 - a student is associated with at most one instructor via *advisor*




Cardinalities in ER Diagrams

- Many to many relationships
 - An instructor is associated with several (possibly 0) students via advisor
 - A student is associated with several (possibly 0) instructors via advisor




Total and Partial Participation

- Total participation (double line)
 - every entity in the entity set participates in at least one relationship in the relationship set
 - i.e., every student must have an advisor
- Partial participation (single line)
 - some entities may not participate in the relationship
 - e.g., not every instructor has to supervise a student




Complex Cardinality Constraints

- Notation for minimum/maximum cardinality of a relation
 - Each student has *exactly one* advisor (i.e., min=max=1)
 - Each instructor can be the advisor of multiple students, but needs not be (i.e., min=0,max=∞)
- Notation:
 - min..max
 - * indicates no limit




Notation of Attribute Types




Expressing Weak Entity Sets

- A weak entity set is depicted via a double rectangle
 - The identifying relationship set is depicted by a double diamond
- The *discriminator* is underlined with a dashed line
 - Primary key for section – (course_id, sec_id, semester, year)



Higher Arity Relationship Sets


- Most relationship sets are binary
- Sometimes, ternary (or higher arity) relations occur
 - ER models support that
- Example:
 - Students work on projects under supervision of an instructor



Cardinality Constraints for Ternary Relations


- Only one single arrow (i.e., cardinality restriction) is allowed for a ternary relation
 - Example: each student can work in at most one project under the supervision of some instructor(s)

why?




Cardinality Constraints for Ternary Relations

- Multiple single arrows (i.e., cardinality restrictions) would lead to different possible interpretations
 - Each student works on at most one project under at most one instructor
 - For each project a student works on, there is at most one instructor
 - For each instructor supervising a student, there is at most one project
- Hence, we do not allow for them




Specialization

- A concept very common in (object oriented) programming
 - Entity sets are sub-/super sets of others
 - They inherit all the attributes from their super sets
- Overlapping
 - A person can be *both* an employee and a student
- Disjoint
 - An employee can be *either* an instructor *or* a secretary




Partial vs. Total Specialization

- Partial specialization
 - An employee may be an instructor or a secretary, or an employee not further specified
 - the default case
- Total specialization
 - There are no other persons than employees and students (in the DB)
 - Needs to be specified in the diagram
 - Analogy in OOP: abstract classes



A Full Example




Reduction to Relation Schemas

- How to get to from an ER model to a relational database model?
 - Recap: relational database models consists of relations
- We have
 - Entity sets and relationship sets
- Goal
 - Translate entity and relationship sets uniformly to *relation schemas*
- Mechanism:
 - For each entity set and relationship set there is a unique relation that is assigned the name of the corresponding entity set or relationship set
 - Each relation has a number of columns (generally corresponding to attributes), which have unique names

Representing Entity Sets


- A strong entity set reduces to a schema with the same attributes
building(name, address)
- A weak entity set becomes a table that includes
the column(s) of the primary key of the identifying strong entity set
room (name, number, capacity)
- At the same time, name is a foreign key
 - which integrity constraints should we use?



Representing Relationship Sets


- Many-to-many relationship sets
 - represented as a relation with attributes for the primary keys of the two participating entity sets
- Example: schema for relationship set *advisor*

advisor = (*student_ID*, *instructor_ID*)




Representing Relationship Sets

- Many-to-many relationship sets
 - additional attributes of the relationship set become attributes of the representing relation
- Example: schema for relationship set *advisor*
advisor = (*student_ID*, *instructor_ID*, *date*)



Representing Relationship Sets

- Special case for one-to-many relationship sets
 - The primary key of the “many” side can become a *foreign key attribute* on the “one” side
- student = (ID, name, tot_cred, instructor_ID)*
- In case of partial participation, this may cause **null** values




Representing Relationship Sets

- Special case for one-to-one relationship sets
 - The primary key on one side can be included on the other side

student = (ID, name, tot_cred, instructor_ID) **or**
instructor = (ID, name, salary, student_id)

why not on both sides?

- In case of partial participation, this may cause **null** values



Representing Attributes

- Composite attributes are flattened out by creating a separate attribute for each component attribute
- Add prefix of super attribute in case ambiguous names occur
 - e.g., street_number, phone_number
- Ignoring multivalued attributes, extended instructor schema is

```
instructor(ID,  
            first_name, middle_initial, last_name,  
            street_number, street_name,  
            apt_number, city, state, zip_code,  
            date_of_birth)
```

<i>instructor</i>
<u><i>ID</i></u>
<i>name</i>
<i>first_name</i>
<i>middle_initial</i>
<i>last_name</i>
<i>address</i>
<i>street</i>
<i>street_number</i>
<i>street_name</i>
<i>apt_number</i>
<i>city</i>
<i>state</i>
<i>zip</i>
{ <i>phone_number</i> }
<i>date_of_birth</i>
<i>age</i> ()

Representing Multi-valued Attributes

- A multivalued attribute M of an entity E is represented by a separate schema EM
- Schema EM has attributes corresponding to the primary key of E and an attribute corresponding to multivalued attribute M
 - Example: Multivalued attribute *phone_number* of *instructor* is represented by a schema:
 $inst_phone = (\underline{ID}, \underline{phone_number})$
- Each value of the multivalued attribute maps to a separate tuple of the relation on schema EM
 - Example: an *instructor* entity with primary key 22222 and phone numbers 456-7890 and 123-4567 maps to two tuples:
(22222, 456-7890) and (22222, 123-4567)


Representing Derived Attributes

- Technically, we can create a view
create view instructor_age **as**
select ID, **NOW()**-date_of_birth **as** age
from instructor

<i>instructor</i>
<u>ID</u>
<i>name</i>
<i>first_name</i>
<i>middle_initial</i>
<i>last_name</i>
<i>address</i>
<i>street</i>
<i>street_number</i>
<i>street_name</i>
<i>apt_number</i>
<i>city</i>
<i>state</i>
<i>zip</i>
{ <i>phone_number</i> }
<i>date_of_birth</i>
<i>age</i> ()

Representing Higher Arity Relations

- Higher arity relationship sets are represented just like binary ones
 - i.e., as one relation with the primary keys of the related entity sets
 - proj_guide(instructor_ID, student_ID, project_ID)




Representing Specialization

- Method 1
 - All three relations become relations
 - primary key is shared
 - Shared attributes are only represented in the higher level entity

person(ID, name, street, city)

employee(ID, salary)

student(ID, tot_credits)
- Drawback:
 - Accessing person information for employees and students requires access to two relations



Representing Specialization


- Method 2
 - All three relations become relations
 - primary key is shared
 - Shared attributes are only represented in each entity

person(ID, name, street, city)

employee(ID, name, street, city, salary)


student(ID, name, street, city, tot_credits)

 - Super relation can be omitted for total specialization
- Drawback:
 - Redundant storage for partial specialization
 - i.e., for persons that are both employees and students



Design Decisions in ER Modeling


- Entity sets vs. attributes



- Entity set
 - Allows for additional information
 - Supports multi-valued attributes
 - in that case, the attribute would end as a relation in the DB anyways

Entity Sets vs. Relationship Sets

- Students register for course sections
 - This could be a simple relationship set as well
- Entity set can store additional information, e.g.
 - Date of registration




Placement of Attributes for 1:1 Relationships

- The primary key on one side can be included on the other side


*student = (ID, name, tot_cred, instructor_ID) or
instructor = (ID, name, salary, student_id)*

- Which one?




Binary vs. Non-Binary Relationships

- Sometimes, non-binary relationships can be replaced by binary ones




Binary vs. Non-Binary Relationships

- Sometimes, non-binary relationships can be replaced by binary ones
 - This is usually the preferred solution




Binary vs. Non-Binary Relationships

- Sometimes, non-binary relationships can be replaced by binary ones
 - but sometimes, they are n-ary by nature




Binary vs. Non-Binary Relationships

- Sometimes, non-binary relationships can be replaced by binary ones
 - but sometimes, they are n-ary by nature



Binary vs. Non-Binary Relationships


- Sometimes, non-binary relationships can be replaced by binary ones
 - but sometimes, they are n-ary by nature
- General decomposition schema:




ER Design Decisions (Summary)

- The use of an attribute or entity set to represent an object
- Whether a real-world concept is best expressed by an entity set or a relationship set
- The use of a ternary relationship versus a number of binary relationships
- The use of a strong or weak entity set
- The use of specialization/generalization – contributes to modularity in the design


Summary of ER Notation




entity set




relationship set




identifying
relationship set
for weak entity set




total participation
of entity set in
relationship



attributes:
simple (A1),
composite (A2) and
multivalued (A3)
derived (A4)




primary key




discriminating
attribute of
weak entity set


Summary of ER Notation (ctd.)




many-to-many
relationship




many-to-one
relationship




one-to-one
relationship




cardinality
limits




role indicator



ISA: generalization
or specialization




total (disjoint)
generalization



disjoint
generalization

Alternative ER Notations

entity set E with
simple attribute A1,
composite attribute A2,
multivalued attribute A3,
derived attribute A4,
and primary key A1




weak entity set



generalization





total
generalization





Alternative ER Notations (ctd.)



many-to-many
relationship





one-to-one
relationship



many-to-one
relationship



participation
in R: total (E1)
and partial (E2)







Alternative Modeling Paradigms: UML

- Unified Modeling Language
 - often used in software design
 - similar scope: objects and their relations
 - ISO standard since 2005
- ER models in RDBMS
 - Direct translation to SQL
- UML models in software engineering
 - Direct translation to source code






Alternative Modeling Paradigms: UML

ER Diagram Notation




Equivalent in UML



!!!

Alternative Modeling Paradigms: UML



<http://pld.cs.luc.edu/database/ER.html>

Summary

- Designing databases
 - i.e., how to get from your customer's requirements...
 - ...to a set of tables and attributes
- ER Models are an intermediate step
 - Conceptual view on the database
 - Graphical notation
 - Can be used for discussion with customers
- Translation rules for ER to RDBMS
- Design decisions
 - For ER Models (mostly business decisions)
 - For translation to RDBMS (mostly computer science decisions)

Questions?

